

Aqua-Hardener 8456

8456

Hardener for Bluefin Pigmolux HQ, for use in **industry**

PRODUCT DESCRIPTION

Product numbers

8456000210



General

Polyisocyanate hardener for all qualities of Bluefin Pigmolux HQ.

Application area

Hardener component for all Bluefin Pigmolux HQ coatings for furniture and interior finishing.



PROCESSING

Processing instructions

- Immediately after adding Aqua-Hardener 8456 (8456) to the paint component, blend in carefully. We recommend waiting approx. 10 minutes before starting work.
- Mixed paints and stains must be processed as specified in the corresponding technical data sheet.

Cleaning the working equipment



8029

To remove dried paint residues we recommend using Aqua-Cleaner (8029) (diluted 1:1 with water).

Please follow our **ARL 150 - Working guidelines for water-based furniture coatings**.

Please refer to the corresponding technical data sheets of the products.

ORDERING INFORMATION

Size of trading unit

500 g, 1 kg, 10 kg

FURTHER DETAILS

Durability / storage



Min. 6 month(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Immediately seal the container to prevent humidity from penetrating.

Close opened containers well and use up the content as soon as possible.

Safety information



The product is only suitable for industrial use.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com**.
